

Power Supply

UL Recognized Power Supply/Charger Boards

Product Number	Description	
AL600ULXB	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, 115VAC input, UL Recognized.	✓
AL400ULXB2	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, 115VAC input, UL Recognized.	✓

UL Listed Power Supply/Chargers with Enclosures

AL125UL	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 1 amp, Class 2 power limited outputs, encl. 8.5"H × 7.5"W × 3.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	✓
AL175UL	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 1.75 amp, Class 2 power limited outputs, encl. 8.5"H × 7.5"W × 3.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	✓
AL400ULX	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, encl. 13.5"H × 13"W × 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), CSFM, MEA & FM Approved.	✓
AL600ULX	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, encl. 13.5"H × 13"W × 3.25"D, 115VAC input, UL Listed (UL294/UL1481), CSFM, MEA & FM Approved.	✓

Access Power Controller (Fused)

AL600ULACM	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H × 12"W × 4.5"D, 115VAC input, UL Listed (UL294), CSFM & MEA Approved.	✓
------------	--	---

Power Conversion Module

VR1	Converts 24VAC or 24VDC input into 12VDC rated @ 1 amp, Modular connector/cable assembly. High-impact insulated housing.	✓
-----	--	---

Batteries

BT126	Lead Acid Battery 12VDC 7AH	✓
-------	-----------------------------	---

Visit midwestwholesale.com for published list prices or contact a sales representative for your pricing.

Power Distribution & Auxiliary Modules

Product Number	Description	
ACM4	4 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into four (4) fused power outputs, individually selectable Fail-Safe/Fail-Secure outputs or dry form "C" contacts, fire alarm disconnect is selectable by output, UL Listed sub-assembly.	✓
ACM8	8 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into eight (8) fused power outputs, individually selectable Fail-Safe/Fail-Secure outputs or dry form "C" contacts, fire alarm disconnect is selectable by output, UL Recognized Component.	✓
PD4UL	4 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into four (4) fused power outputs, UL Recognized.	✓
PD8UL	8 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into eight (8) fused power outputs, UL Recognized.	✓
PD16W	16 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into sixteen (16) fused power outputs, UL Recognized.	✓

Programmable Timers

6062	Multi-Function Timer - 12VDC or 24VDC operation, SPDT contacts rated @ 8 amp/115VAC, 1 sec. to 60 min. adjustable timing range. One second momentary relay activation at the end of timing cycle.	✓
PT724A	DIN Rail Mountable Annual Event Timer - 12 to 24 volt AC or DC operation, SPDT contact rated @ 10 amp/115VAC/28VDC, 365-day/24-hr. timer, LCD display, Programmable features: 50 individual daily/weekly events, 350 block events per week, 10 holiday dates.	✓

Relay Modules

RBST	Relay Module - 6VDC, 12VDC or 24VDC operation, 30mA current draw, DPDT contacts rated @ 1 amp/120VAC or 2 amp/28VDC.	✓
RBSNTTL	Sensitive Relay Module - 12VDC to 24VDC operation, 3VDC to 24VDC isolated positive or negative trigger input, 18mA current draw, DPDT contacts rated @ 1 amp/120VAC or 2 amp/28VDC.	✓

Visit midwestwholesale.com for published list prices or contact a sales representative for your pricing.